

SM 215E MODEL GARBAGE DISPOSAL

TECHNICAL DATA

Manufacturer: Copmak Teknolojik Mutfak Aletleri ve Sanayi Ticaret Limited Sirketi

Address: Ikitelli Organize Sanayi Bolgesi Mutfakcilar Sanayi Sitesi M5 Blok No36 Basaksehir/
Istanbul / Turkey

Telephone: +90 554 70 70 Pbx Customer Service 444 9 040 Gsm + 90 533 206 79 96

Communication: info@copmak.com.tr www.copmak.com.tr

Production Site: Turkey

Product Name: Garbage Disposal Machine

Brand: Copmak

Certificates: CE Certificate, IP65 waterproof power box certification

Type: With Stainless Cabinet

Engine: 2 Hp 2800 Rpm

Energy: 220/240 Volt 50/60Hz Hz 1,5 kW Single Phase 1~ 1N 1P and other barcoded energy options

Blade System: 304 Quality Stainless Steel

Garbage Inlet: 160 mm with magnet

Security Warning: Audio and light warning positioned on the device

First Run: Pneumatic Button

Protection: Safety thermal protection against overload

Capacity: 400 kg per hour, Kitchens that do not exceed 600 people

Plumbing Clean Water: Cold water line with 1/2 valve

Energy Installation: 3x2.5 mm TTR power cable under the sink H 400 mm 30 Ampere Fuse per line

Waste Water Plumbing: PVC pipe with a diameter of at least 50 mm and a maximum height of 250 mm under or behind the cabinet.

Gross Net Weight:

Box Size: 700x700x900 mm

20-foot Container Quantity:

ST 315E MODEL GARBAGE DISPOSAL

TECHNICAL DATA

Manufacturer: Copmak Teknolojik Mutfak Aletleri ve Sanayi Ticaret Limited Sirketi

Address: Ikitelli Organize Sanayi Bolgesi Mutfakcilar Sanayi Sitesi M5 Blok No36 Basaksehir/
Istanbul / Turkey

Telephone: +90 554 70 70 Pbx Customer Service 444 9 040 Gsm + 90 533 206 79 96

Communication: info@copmak.com.tr www.copmak.com.tr

Production Site: Turkey

Product Name: Garbage Disposal Machine

Brand: Copmak

Certificates: CE Certificate, IP65 waterproof power box certification

Type: With Stainless Cabinet

Engine: 3 Hp 2900 Rpm

Energy: 400 Volt 50Hz Hz 2,2 kW Three Phase 3~ 1N 1P and other barcoded energy options

Blade System: 304 Quality Stainless Steel

Garbage Inlet: 160 mm With Magnet

Security Warning: Audio and light warning positioned on the device

First Run: Pneumatic Button

Protection: Safety thermal protection against overload

Capacity: 500 kg per hour, Kitchens that do not exceed 750 people

Plumbing Clean Water: Cold water line with 1/2 valve

Energy Installation: 5x2.5 mm TTR power cable under the sink H 400 mm 25 Ampere Fuse per line

Waste Water Plumbing: PVC pipe with a diameter of at least 50 mm and a maximum height of 250 mm under or behind the cabinet.

Gross Net Weight:

Box Size: 700x700x900 mm

20-foot Container Quantity: